

# MATERIAL SAFETY DATA SHEET

## **SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Polycell Brush Cleaner (502205) **Product Name:** 

Kansai Plascon (Pty) Ltd **Company Name:** 

Address: P.O. Box 4010 Luipaardsvlei

1743

Telephone: (011) 951 4500 Facsimile: (011) 955 2841 **Contact Person:** Mr. C.Costa

#### **SECTION 2. COMPOSITION/INFORMATION ON INGREDIENTS**

**Chemical Class:** Organic solvent

Classification: F, Xn

R Phrases: R11, 20, 41, 67 S2, 13, 16, 51, 62 S Phrases:

Hazardous and/or other relevant Components	% (w/w)	CAS No.	E.C. No.
TOLUENE	< 12.5	108-88-3	601-021-00-3
BUTYL ALCOHOL	< 5	71-36-3	603-004-00-6

#### **SECTION 3. HAZARDS IDENTIFICATION**

**SAPMA Health Rating:** 2-MODERATE - Temporary or minor injury possible even if treatment given

Inhalation: Harmful. Excessive exposure must be avoided.

Skin: Irritating, risk of dermatitis.

Eyes: Highly Irritating and risk of irreversible damage. Ingestion: Harmful mat cause lung damage if swallowed.

No carcinogenic, mutagenic or genetic effects established

May have short-term environmental effects. Contain, monitor & remove.







#### **SECTION 4. FIRST AID MEASURES**

Inhalation: Move to fresh air. In case of discomfort seek medical attention.

Use hand cleaner/soap and water. Remove contaminated clothing. If any discomfort, get medical attention. Skin:

Eyes: Rinse immediately with plenty of water. Refer immediately to doctor.

Ingestion: Wash mouth with plenty of water. Do NOT induce vomiting. Seek immediate medical attention.

## **SECTION 5. FIRE FIGHTING MEASURES**

Highly Flammable with toxic fumes.

Containers can burst in a fire. Can form explosive vapour/air mixture. Static discharge hazard.

Use foam, dry powder. Use fog to cool and control. Do NOT use water jets.

Cool containers in case of fire.

### SECTION 6. ACCIDENTAL RELEASE MEASURES - SEE ALSO SECTIONS 5, 8, 13

Contain & collect spillage with non-combustible absorbent material and dispose of according to local regulations.

Do not use sawdust

Do not allow product to enter drains and sewers.





# MATERIAL SAFETY DATA SHEET

#### **SECTION 7. HANDLING AND STORAGE**

Keep away from ignition sources. No smoking. No sparks.

Store away from direct sun and heat.

Keep containers cool. Avoid free fall of liquid – use earthing.

#### **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

NAME	CAS	OEL (mg/m <sup>3</sup> )	OEL (ppm)	STOEL (mg/m³)	STOEL (ppm)
TOLUENE	108-88-3	199	50	560	150 RL + S
BUTYL ALCOHOL	71-36-3	150	50	150	50 RL S

(CL/RL = Controlled/Recommended level 'S' = Skin annotation)

**SAPMA Rating:** 2-H-E PPE - Respirator and Eye protection

**Inhalation:** In case of insufficient ventilation, use suitable respiratory protection.

**Skin:** Avoid contact. Use barrier cream and impervious gloves.

**Eyes:** Use face shield or goggles. Avoid direct contact.

**Ingestion:** Observe the rules of hygiene. Wash before eating, drinking or smoking.









#### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance: Clear liquid

Boiling Point: > 35 °C

Flash Point: < 23 °C

Density: 0.86 (typical)

Solubility: Insoluble in water

# SECTION 10. STABILITY AND REACTIVITY

Stable under normal conditions
Avoid ignition sources – flames, sparks, static and heat.
Inert - no reaction with fire-fighting water
Could generate static – use earthing

## **SECTION 11. TOXICOLOGICAL INFORMATION**

No carcinogenic, mutagenic or genetic effects established LD50 Oral: T.B.E.

# SECTION 12. ECOLOGICAL INFORMATION

May have short-term environmental effects. Contain, monitor & remove.

#### **SECTION 13. DISPOSAL INFORMATION**

Use reputable waste disposal contractors. Exercise caution in disposal of used containers.

## **SECTION 14. TRANSPORT INFORMATION**

SIN/UN Number: 1263

Shipping Name: PAINT RELATED MATERIAL

Packaging Group: II Class: 3





# **MATERIAL SAFETY DATA SHEET**

## **SECTION 15. REGULATORY INFORMATION**

#### Classification: F Flammable, Xn Harmful

- R11 Highly Flammable
   R20 Harmful by inhalation
   R41 Risk of serious damage to eyes
   R67 Vapours may cause drowsiness or dizziness
- Vapours may cause drowsiness or dizziness

  Keep out of the reach of children (Retail sales only)

  Keep away from food, drink and animal feeding stuffs

  Keep away from sources of ignition No smoking
- S51 Use only in well ventilated areas
- S62 If swallowed, do not induce vomiting, seek medical advice immediately and show container or label.

## **SECTION 16. OTHER INFORMATION**

Take precautionary measures against static discharges. In case of any discomfort always seek medical advice.

All information is given in good faith but without guarantee in respect of accuracy. No responsibility is accepted for errors or omissions or the consequences thereof.

